

# NorFlute® Medium

NORPAC's NorFlute Medium is our standard for quality, consistency, and runnability. NORPAC has a long-standing history of delivering superior products with exceptional service to the domestic and international marketplace. With dedicated development teams, strict quality control measures, and responsive technical service, you can expect consistent quality and reliability from NORPAC.

			Targets				
<b>Basis Weight*</b>	TAPPI 410	lbs/MSF	23	26	28	30	33
<b>Basis Weight</b>	TAPPI 410	GSM	112	127	140	146	161
<b>Moisture</b>	TAPPI 412	%	9.0	9.0	9.0	9.0	9.0
<b>STFI (CD)</b>	TAPPI 826	lbf/inch	12	12.5	13	14	14.6
<b>Ring Crush</b>	TAPPI 822	lbf/inch	30	35	40	45	51
<b>Concora CMT</b>	TAPPI 809	lbf/inch	48	50	51	52	54

\*Expected BWT is nominal +/- 1 lb/MSF.

Moisture range +/- 2.0%.

NorFlute 18# and 21# are also available.

Please contact your NORPAC representative to discuss availability.

## ATTRIBUTES

- Uniform moisture profile
- Consistent basis weights
- Excellent formation
- Great two-sided uniformity
- Reliable strength and glueability

## END USES

- Consumer durable packaging
- Shipping containers
- Packaging and inserts
- POP displays

## ENVIRONMENTAL PERFORMANCE

- SFI® Certified Sourcing, FSC® Controlled Wood, and PEFC Controlled Sources
- California Transparency in Supply Chains Act compliance
- High-efficiency, low emission and water use manufacturing process
- U.S. FDA compliant

**NORPAC**  
**PACKAGING**

## CONTACT INFORMATION

[www.norpacpaper.com/products](http://www.norpacpaper.com/products) [sales@norpacpaper.com](mailto:sales@norpacpaper.com) 1-800-426-0866



Please Recycle



Proudly made by NORPAC  
in Longview, WA, USA