

NorFlute® Medium

NORPAC's NorFlute Medium is our standard for quality, consistency, and runnability. NORPAC has a long-standing history of delivering superior products with exceptional service to the domestic and international marketplace. With dedicated development teams, strict quality control measures, and responsive technical service, you can expect consistent quality and reliability from NORPAC.

PRODUCT INFORMATION

TEST	TAPPI TEST METHOD	All values are reel averages.				
Basis Weight*	T410	Nominal	23	26	28	30
Concora CMT	T809	Typical	48	50	51	52
		Rejected Below	40	45	46	47
STFI (CD)	T826	Typical	12.0	12.5	13	14
		Rejected Below	10.8	11.5	12	12
Ring Crush	T822	Typical	30	35	40	45
		Rejected Below	25	30	35	40
Average Moisture	T412	Target	8.5	8.5	8.5	8.5
		Range	+/- 2.0%			

*Expected BWT is nominal +/- 1 lb/MSF.

NorFlute is also available in 10, 14, 16, 18, and 21 lbs/MSF with 8.5% moisture.

PRODUCT ATTRIBUTES

- Uniform moisture profile
- Consistent basis weights
- Excellent formation
- Great two-sided uniformity
- Reliable strength and glueability
- Maximum roll diameter:
50 inches/1270 mm
- Maximum roll width:
106 inches/2692 mm

END USES

- Consumer durable packaging
- Shipping containers
- Packaging and inserts
- POP displays

ENVIRONMENTAL PERFORMANCE

- SFI® Certified Sourcing, FSC® Controlled Wood, and PEFC Controlled Sources
- California Transparency in Supply Chains Act compliance
- High-efficiency, low emission and water use manufacturing process
- U.S. FDA compliant

CONTACT INFORMATION

www.norpacpaper.com/products sales@norpacpaper.com 1-800-426-0866



Please Recycle



Proudly made by NORPAC
in Longview, WA, USA